Tel/tronix[®]

Video Quality Monitors

Sentry ABR • VNM-SABR2 Datasheet



Monitor your entire network with rich graphs and an easy-to-use web-based interface.

Features

- Supports up to 250 Top Manifests
- Supports Apple's HTTP Live Streaming, Adobe's HTTP Dynamic Streaming, Microsoft's Smooth Streaming and MPEG DASH Protocols with HTTP statistics
- ABR Decryption and DRM Support provides QoE and PVQ measurements for decrypted and decoded video and audio
- Proactively monitors all available ABR "media" and "network" from content acquisition (source) to the edge of the network
- Fetches manifest files and fragments from any place on the network to simulate a subscriber's request for content
- Validates all assets, bitrate profiles and manifest files based on a highly parallel HTTP fragment fetching engine
- Performs sub-stream manifest validation and fragment fetching in real time at the manifest-indicated rate
- Alerts on any mismatch in the bitrate of the sub streams; missing segments (HTTP errors); and excessive segment-fetching latency

- Reports on the availability of all input manifests (programs) over the network, and their sub streams in the familiar Sentry-product style
- Supports both 1 GbE and 10 GbE interfaces allowing Sentry ABR to be placed throughout the network for maximum ABR monitoring coverage

Benefits

- Quality of experience and perceptual video quality measurements from ingress to final delivery for multiscreen, OTT, TV Everywhere services
- Quantify and compare video quality across profiles
- Reduce operational costs
- Ensure customer satisfaction

End to end video quality monitoring with **Sentry ABR**

Sentry® ABR is part of Tektronix' end-to-end video quality and service assurance solution for monitoring OTT (Over The Top), TV Everywhere and multiscreen services. Sentry ABR provides a comprehensive and scalable monitoring solution for post-fragmented adaptive bit rate (ABR) streams and supports both 1 GbE and 10 GbE interfaces for maximum ABR monitoring coverage throughout the network.

Sentry ABR supports up to 250 top manifests which translates into a much higher monitoring capacity as each manifest can support up to 15 representations of each program. Sentry ABR proactively monitors all available ABR "media" and "network" from content acquisition (ingress) to final delivery. Sentry ABR offers ABR decryption and DRM support, which enables Quality of Experience (QoE) and Perceptual Video Quality (PVQ) measurements for decrypted and decoded video and audio content.

Manifest files and fragments can be fetched from any place on the network (e.g., origin servers or CDN caching servers) to simulate a subscriber's request for content. Sentry ABR validates all assets, bitrate profiles, and manifest files based on a highly parallel HTTP fragment fetching engine. In addition, it supports all of the existing alert functionality and reporting capabilities offered in Sentry (including the alert dashboard, program availability and 90-day historical reporting and trending analysis). This enables proactive and comprehensive QoS and QoE monitoring of all video assets for ABR streaming. ABR issues are identified quickly and often resolved before customers are impacted.

Multi-Screen Multi-Point Video Monitoring Sentry Sentry ABR Computer **Fragment** Origin **CDN Transcode** & DRM Server Smartphone **Tablet ABR Video Distribution ABR Video Content** (Over HTTP) **Preparation** Live, VOD OTA content Sentry ABR Sentry Asset & Network Validation Content Validation Caching & Origin Transcode Streaming & DRM **Content Delivery Content Preparation** Video Ingest

Post transcode monitoring with Sentry

- Availability of all services, profiles/bitrates
- QoE Scoring
- Verify Audio Quality
- Perceptual Video Quality, check for over-compression artifacts
- IDR/EBP presence, cadence and alignment
- Compliance for Audio Loudness and Closed Captions

ABR content delivery with Sentry ABR

- HLS, HDS, DASH and MS-SS support
- · ABR decryption and DRM support
- HTTP errors
- Manifest file verification
- Service and Profile availability
- · Fragment size and bitrate
- Fragment load time and latency time
- Historical graphing/trending of KPI's

Characteristics

All specifications apply to all models unless noted otherwise.

General

Browser Support	Firefox, Safari, Google Chrome and Internet Explorer
MPEG/IP Input Port	1000BASE-T Ethernet interface 10GBASE-(LR or SR) interface
Management port	1000BASE-T Ethernet interface

Supported protocols

Video	MPEG-2, H.264, H.265, VC-1		
Audio	Dolby AC-3 (5.1 Surround), E-AC-3		
	MPEG-1 Layer II (Mono, Stereo)		
	AAC, HE-AAC, and HE-AAC v2		
Network	HTTP over TCP/IP		
	SNMP trap and MIB support		

Physical

im		

Height	44 mm (1.73 in)	
Width	437 mm (17.2 in)	
Depth	600 mm (29.5 in)	
Weight (net)	12.4 kg (27 lb.)	
Power supply	100-240 V AC, 50-60 Hz	

Environmental

Temperature

+10°C to +35°C, 30°C per hour maximum gradient Operating

Temperature of the intake air at the front and sides of the instrument

Non-operating -20°C to +60°C, 30°C per hour maximum gradient

Power 4.0-1.7 A maximum, 100 - 240 V, 50/60 Hz

The maximum power consumption for any board combination measured is 175 W at 120 V by safety test

ϵ



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

ASEAN / Australasia (65) 6356 3900 Belgium 00800 2255 4835* Central East Europe and the Baltics +41 52 675 3777 Finland +41 52 675 3777 Hong Kong 400 820 5835 Japan 81 (3) 6714 3086 Middle East, Asia, and North Africa +41 52 675 3777 People's Republic of China 400 820 5835 Republic of Korea +822 6917 5084, 822 6917 5080 Spain 00800 2255 4835* Taiwan 886 (2) 2656 6688 Austria 00800 2255 4835*
Brazil +55 (11) 3759 7627
Central Europe & Greece +41 52 675 3777
France 00800 2255 4835*
India 000 800 650 1835
Luxembourg +41 52 675 3777
The Netherlands 00800 2255 4835*
Poland +41 52 675 3777
Russia & CIS +7 (495) 6647564
Sweden 00800 2255 4835*
United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Canada 1 800 83 9200
Denmark +45 80 88 1401
Germany 00800 2255 4835*
Italy 00800 2255 4835*
Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
Norway 800 16098
Portugal 80 08 12370
South Africa +41 52 675 3777
Switzerland 00800 2255 4835*

USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tek.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

10 Jul 2017 2CW-61220-1

www.tek.com

